AMENDMENTS TO THE CLAIMS

Please replace the claims with the following revised listing:

1. (Original) A reactor for processing a hazardous gas using a non-thermal plasma and a dielectric heat produced when the non-thermal plasma is produced, the reactor comprising: a body having an inlet and an outlet;

a plurality of planar electrodes arranged parallel in the body and spaced apart from each other at a certain interval, in which the plurality of planar electrodes are alternately connected to an alternating current power, and a ground such that every other planar electrode is connected to the alternating current power and the remaining planar electrodes are connected to the ground; and

a power supply unit for applying a voltage of an alternating current frequency to the planar electrodes.

- 2. (Original) The reactor as claimed in claim 1, wherein each of the planar electrodes comprises a first dielectric plate and a second dielectric plate, a first side of each of the first and second dielectric plates being coated with a metallic thin film and a second side of each of the first and second dielectric plates being coated with a catalyst, and the first and second dielectric plates being adhered such that the metallic thin film of the first dielectric plate faces to the metallic thin film of the second dielectric plate.
- 3. (Original) The reactor as claimed in claim 2, wherein each of the dielectric plates has a thickness of 0.1 to 2 mm.

- 4. (Original) The reactor as claimed in claim 2, wherein the dielectric plate comprises any one selected from the group consisting of ceramic, glass, and quartz.
- 5. (Original) The reactor as claimed in claim 2, wherein the catalyst is a metallic catalyst- containing at least one metal element selected from the group consisting of Pt, Pd, V, and Rh..
- 6. (Original) The reactor as claimed in claim 2, wherein the catalyst is a zeolite catalyst containing at least one zeolite selected from the group consisting of MS 5A and MS 3A.
- 7. (Original) The reactor as claimed in claim 2, wherein the catalyst is a photo catalyst containing TiO₂.
- 8. (Original) The reactor as claimed in claim 1, wherein the power supplied to each of the planar electrodes by the power supply unit is an alternating current voltage of 1 kV to 30 kV at a frequency of 50 Hz to 100 kHz.
- 9. (Original) The reactor as claimed in claim 1, wherein each of the planar electrodes comprises two dielectric plates, a metallic thin film interposed therebetween, and a catalyst layer coated on an outer surface of each of the dielectric plates which is opposed to an inner surface facing the metallic thin film.

- 10. (Original) The reactor as claimed in claim 9, wherein each of the dielectric plates has a thickness of 0.1 to 2 mm.
- 11. (Original) The reactor as claimed in claim 9, wherein the dielectric plate comprises any one selected from the group consisting of ceramic, glass, and quartz.
- 12. (Original) The reactor as claimed in claim 9, wherein the catalyst is a metallic catalyst- containing at least one metal element selected from the group consisting of Pt, Pd, V, and Rh..
- 13. (Original) The reactor as claimed in claim 9, wherein the catalyst is a zeolite catalyst containing at least one zeolite selected from the group consisting of MS 5A and MS 3A.
- 14. (Original) The reactor as claimed in claim 9, wherein the catalyst is a photo catalyst containing TiO₂.
 - 15. 17. (Canceled)